



8000T All-Temp

Permanent labels

Thermal transfer

Description

An ultra smooth coated white paper label stock, 8000T All-Temp produces excellent quality images, including rotated barcodes, graphics and small characters, at print speeds up to 254mm per second. Top quality permanent acrylic adhesive offers strength and excellent adhesion on a wide range of surfaces over a wide variety of temperatures. Compatible with Zebra 2100, 2300, 5319 and 3400 series ribbons. Suitable for use with Zebra 3200 ribbons in applications where improved smear and scratch resistance is required.

Suggested Applications

- Long-term labelling where temperatures can fluctuate
- Labelling of packaging materials, including corrugated, plastic and metal
- Cold temperature storage labelling
- Work-in-Process labelling, where varying temperatures apply
- LOGMARS, AIAG, HIBC labelling
- Shipping and address labels

Technical Specifications

	Description	Caliper
Facestock	73gsm ultra smooth white coated paper	74 microns
Adhesive	Permanent acrylic based	18 microns
Liner	70lb semi bleached Kraft stock	64 microns
		Total 156 microns

Recommended Zebra printers: Desktop, mid-range and high-performance thermal printers

Recommended Zebra Ribbons: 2300, 2100, 5319, 3400, 3200

Minimum application temperature: -8°C

Service temperature range: -40°C to 93°C

Recommended storage conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the Zipship price list or order sample roll SAM5024.