



Z-Perform 1000T

Permanent labels

Thermal transfer

Description

Z-Perform 1000T is an uncoated, supercalendered thermal transfer paper label stock, which produces scannable bar codes and acceptable images when matched with Zebra 2300, 2100 and 5319 ribbons on Zebra thermal transfer printers. The general purpose permanent acrylic based adhesive offers high initial tack and adhesion on corrugated packaging materials for applications of less than three years (indoor usage).

Suggested Applications

- Labelling of packaging materials e.g. boxes, pallets in logistics applications
- Product identification
- Picking and receiving labels in warehousing applications
- Work-in-progress labelling
- Compliance labelling
- Shipping labels

Technical Specifications

	Description	Caliper
Facestock	75gsm white uncoated paper	70 microns
Adhesive	Permanent acrylic based	26 microns
Liner	62gsm Glassine liner	56 microns
		Total 152 microns

Recommended Zebra printers: Desktop, mid-range and high-performance thermal transfer printers

Recommended Zebra Ribbons: 2300, 2100, 5319

Minimum application temperature: 0°C

Service temperature range: -20°C to 80°C

Recommended storage conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the Zipship price list or order sample roll SAM5147.