



Z-Perform 1000T 190 Tag

Paper tag

Thermal transfer

Description

A smooth, uncoated 175 micron matt white thermal transfer tag stock with excellent ink receptivity, specially designed for use with Zebra 2300, 2100 and 5319 thermal transfer ribbons. If extra scratch and smear resistance is required, Zebra 3400 and 3200 thermal transfer ribbons are recommended.

Suggested Applications

- Inventory control and shop floor (work-in-progress) tracking tickets.
- AIAG, LOGMARS and industrial inventory control tags.
- Packaging inserts or pallet tags
- Shelf edge tickets
- Visitor name tags
- Admission tickets

Technical Specifications

| Description | | Caliper |
|-------------|-----------------------------|-------------------|
| Facestock | 190gsm white uncoated paper | 175 microns |
| | | Total 175 microns |

Recommended Zebra printers: Mid-range and high-performance thermal printers (testing is strongly recommended on desktop printers)

Recommended Zebra Ribbons: 2300, 2100, 5319, 3400, 3200

Minimum application temperature: N/A

Service temperature range: -46°C to 93°C

Recommended storage conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAM5284.