



SEE MORE. DO MORE.

PolyO 3100T

Permanent labels

Thermal Transfer

Description

A white, satin finished, corona treated co- extruded polyolefin film. When combined with Zebra's 5095 resin ribbon it is BS5609 approved and produces outstanding print quality. The all weather adhesive offers excellent tack and adhesion on apolar, slightly rough surfaces. The product combines the benefits of a flexible label with good rigidity and dispensing.

Suggested Applications

- Chemical drum labelling
- Labelling in "hot-fill" production lines
- Post blow-mould labelling
- Labelling in environmentally sensitive areas
- Cosmetic and toiletries labelling which require high quality graphics

Technical Specifications

	Description	Caliper
Facestock	Satin coated polyolefin film	75 microns
Adhesive	Rubber based, permanent adhesive	16 microns
Liner	White Glassine liner	63 microns
	Total	154 microns

Recommended Zebra printers: mid-range and high-performance thermal transfer printers

Recommended Zebra ribbons: 3200, 4800, 5095

Minimum application temperature: 5°C

Service temperature range: -20°C to +80°C

Recommended storage conditions: One year duration when stored at approx 22°C/ 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order SAMPLE5151.



SEE MORE. DO MORE.

