



Zebra® Kiosk Print Station



SEE MORE. DO MORE.



A Low-Cost Self-Service Kiosk Solution

An innovative, off-the-shelf, all-in-one kiosk solution, the Zebra Kiosk Print Station makes it easy and affordable to bring the benefits of self-service—like improved sales, greater customer satisfaction and reduced costs—to your business. The Zebra Kiosk Print Station accessory accommodates a Zebra® kiosk printer, a roll of Zebra media and a compact kiosk computer to form a complete, economical alternative to expensive custom kiosks. Simply add software to complete the solution.

- **Quick and Easy to Integrate**—Integrates all the kiosk hardware components into an easy-to-install device that simply mounts to a wall or pole.

- **Easy to Afford**—Its low cost results in rapid ROI, so even smaller businesses can reap the benefits of self-service kiosks.
- **Flexible Media Options**—The Zebra Kiosk Print Station supports up to 6" diameter media rolls and widths of 2.3"/58 mm to 3.25"/82.5 mm.
- **Durable and Secure**—A sturdy, metal, lockable enclosure securely holds the printer and media, and a kiosk computer securely fastens to the unit—protecting all components from tampering and tough retail environments.
- **Easy to Service**—Enclosure opens completely to provide easy access for quick media changes and service.

Now it's convenient and affordable for any size business application to implement a self-service kiosk solution

An innovative, off-the-shelf and ready-to-ship kiosk solution

Installs anywhere, pole- or wall-mountable

So affordable, it's perfect for retail businesses of any size

Accommodates a reliable Zebra TTP 2000™, KR403™ or KR203™ kiosk printer

SPECIFICATIONS AT A GLANCE*

Zebra Kiosk Print Station**



Standard Features

- All-in-one cost-effective solution for self-service applications
- Innovative design integrates kiosk hardware components
- Locking enclosure secures printer and media
- Ultra-compact design and pole or wall mount saves floor space
- Robust, heavy-duty metal frame with sturdy plastic enclosure
- Supports up to 6" diameter media rolls in various widths

Peripherals and Accessories

- Kiosk computers with VESA 75/100 Standard mounting
- Max computer width 17.6" (448 mm) with horizontal centerline mounting. Distance from the center of the VESA mounting holes to the printer tower is 8.8" (224 mm)

Supported Printers

- Zebra TTP 2010 serial kiosk receipt printer
- Zebra TTP 2030 USB kiosk receipt printer
- Zebra KR203 USB kiosk receipt printer
- Zebra KR403 USB and serial receipt printer

Supported Print Features

- Zebra patented looping presenter feature
- Paper low sensor (optional)

Accessories

- Printer power supply
- AC power cord
- USB or serial communication cable
- Paper guide: 2.3"/58 mm, 2.4"/60 mm, 3.15"/80 mm and 3.25"/82.5 mm

Media Options

Supported Media

- Widths: 2.3"/58 mm, 2.4"/60 mm, 3.15"/80 mm and 3.25"/82.5 mm
- Up to 6" diameter media roll
- 1" media core

Mounting Options

- Zebra Kiosk Print Station: pole or wall-mount
- Third-party kiosk computer: Conforms to the VESA 75/100 mm Standard

Environmental

- European RoHS compliant
- For indoor use only

Physical Characteristics

- Width: 18.2"/462 mm
- Height: 16.2"/411 mm
- Depth: 8.5"/216 mm
- Weight: 13.4 lbs/6.1 kg
- Weight with printer, 6" diameter roll of media, printer power supply (excludes computer and computer power supply): 20.4 lbs/9.3 kg

Warranty

One year limited

Zebra Kiosk Printer**



Standard Features

- Direct thermal receipt printing
- Looping presenter with pull detector
- Full-width or partial guillotine
- Auto media loading
- USB or serial connectivity
- Windows® drivers for plug and play and direct addressing with ESC commands

Printer Models

- TTP 2010 (serial), TTP 2030 (USB), KR403 (Serial and USB), KR203 (USB)

Printer Specifications

- Resolution: 203 dpi/8 dots per mm
- Maximum print width: 2.8"/72 mm
- Minimum print length: 2.76"/70 mm
- Maximum print length: 23.6"/600 mm
- Maximum print speed: 6"/150 mm per second

Media Specifications

- Paper widths: 2.28"/58 mm, 2.36"/60 mm, 3.15"/80 mm and 3.25"/82.5 mm
- Maximum diameter of media roll: 6"/152 mm
- Minimum diameter of media core: 1"/25 mm
- Media thickness: 0.002"/0.054 mm to 0.004"/0.11 mm
- Media types: Roll paper

Operating Characteristics

Environmental

- Operating temp: 14° F/-10° C to 122° F/50° C
- Storage temp: 14° F/-10° C to 122° F/50° C
- Operating humidity: 10% to 95% RH non-condensing
- Storage humidity: 10% to 95% RH non-condensing excluding paper

Physical Characteristics

- Width: 4.1"/105 mm
- Height: 2.6"/65 mm
- Depth: 5.7"/145 mm
- Weight: 2.4 lbs/1.1 kg

Electrical

24VDC +/-5%, average of 2A when printing (85mA idle)

Warranty

One year limited

**Printer, accessories and media sold separately from the Kiosk Print Station.



Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
apacchannelmarketing@zebra.com

EMEA Headquarters
+44 (0)1628 556000
mseurope@zebra.com

Latin America Headquarters
+1 847 955 2283
inquiry4@zebra.com

Other Locations / USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam **Latin America:** Argentina, Brazil, Colombia, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

*Specifications subject to change without notice.

©2013 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. All rights reserved. Windows is either a registered trademark or trademark of Microsoft Corporation. All other trademarks are the property of their respective owners.

P1011385 Rev. 4 (03/13)