



SEE MORE. DO MORE.

Z-Select 2000D 60 Receipt

Receipt Paper

Direct Thermal

Description

A topcoated direct thermal 60 micron white receipt paper, which produces high contrast black images with Zebra kiosk printers. Z-Select 2000D 60 Receipt has very good environmental resistance to factors such as heat, humidity, light, plasticizer and water. Direct thermal material is not recommended for applications involving prolonged exposure to moisture and solvents or long term exposure to heat UV light sources. When stored correctly*, the printed image can be expected to remain legible for up to 12 years.

Suggested Applications

- Voucher and coupon printing
- Queue management tickets
- Receipts for retail applications
- Toll receipts
- ATM tickets/ receipts
- Car rental and hotel check-in tickets

Technical Specifications

| | Description | Caliper |
|-----------|-----------------------------------|------------------|
| Facestock | 58gsm white thermal imaging paper | 60 microns ±8% |
| | | Total 60 microns |

- Recommended Zebra printers:** RW and MZ kiosk printers
- Recommended Zebra ribbons:** N/A
- Service temperature range:** -5°C to 49°C
- Recommended storage conditions:** 6 months duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

*Zebra expects, but does not warrant, that printed images on those supplies products where an archive life is listed under key features can be expected to last as stated, when stored according to specific archive conditions. Please refer to www.accesszebra.com for further information. Zebra's standard Terms and Conditions of Sale apply for all sales of Zebra products.



SEE MORE. DO MORE.

For testing of this material, please order SAMPLE66893-K.

