

Product data**FASSON PB Vellum Extra / S2000N / BG40 white / S2000N / BG40 brown**No Imprint / **ADA747**

EAN Code : 8712739222524

Spec Code :

Issue date : 26-Jul-2006

Facestock

A white, surface-sized, supercalendered woodfree printing paper.

Basis Weight	73g/m ²	ISO 536
Caliper	0.071mm	ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

BG40 white, a supercalendered glassine paper.

Basis Weight	60g/m ²	ISO 536
Caliper	0.055mm	ISO 534

2nd Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

Basis Weight	60g/m ²	ISO 536
Caliper	0.055mm	ISO 534

Laminate

Total Caliper	0.237mm	+/- 10 %
---------------	---------	----------

PERFORMANCE DATA

Initial Tack	700N/m	FTM 9 glass
Peel Adhes. 90°	300N/m	FTM 2 st.st.
Min. appl. temp.	0 °C	
Service temp.	-20 °C --> +80 °C	

Adhesive performance

The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

The favourable adhesive properties allow the product to be used on a wide range of flat and curved substrates, including packaging materials such as cardboard, plastic films and HDPE containers.

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry, non fatty foodstuffs.

Application and use

Decorative or functional label applications where a second (or third) self-adhesive label is needed when the first layer has been peeled off or applied, eg promotional stickers on consumer products and direct mail.

Conversion / Printing

The surface of this paper is specially suited to single and/or multicolour line or process printing by letterpress, offset, flexo, screen and hot foil stamping. Offers superior print characteristics where a gloss surface finish is not required.

This layout has to be converted at low speed.

Shelf life

Two years, stored at 22°C / 50% RH.

N.B. : All data to be considered as typical values.



Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue credit in such amount as it deems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.