

METAPACE

Metapace L-42DT - Highly flexible all-rounder for the desktop

www.metapace.com

Highlights

- Affordable direct thermal/thermal transfer desktop label printer
- Extremely fast printing, with up to 178 mm/sec.
- Compact housing, large Flash and RAM memory
- Versatile connectivity: USB, RS232, parallel, optional Ethernet and Wi-Fi
- Complete package with accessories, just unpack and start

Technical specifications

Print

Printing method	Direct thermal/Thermal transfer
Print width	max. 108 mm
Print length	6 – 2000 mm
Print speed	max. 178 mm/sec.
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi) (optional)

Media

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	20 – 110 mm
Roll diameter	max. 130 mm
Core diameter	25.4 – 38.1 mm
Media strength	0.06 – 0.2 mm

Ribbon

Ribbon width	110 mm
Ribbon length	max. 74 m
Core diameter	12.7 mm

Electronics

Memory	Flash: 128 MB, RAM: 64 MB
Interfaces	USB 2.0, serial, parallel, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2.5A
Barcodes	All Standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months; Auto-Cutter: min. 6 months; TPH: min. 6 months

Software

Emulation	EPL (compatible), EPL II (compatible), ZPL (compatible), ZPL II (compatible), SLCS
Drivers	Windows 8 / 7 / VISTA / XP / 2012 Server / 2008 Server / Linux / Mac OS X
Labeldesigner	Metapace Label Designer Software

Specifics

Options	Auto-Cutter, Dispenser, Ethernet, WiFi, external media holder
---------	---

Warranty

Period	24 months
--------	-----------

Housing

Dimension (WxHxD)	200 × 252 × 173 mm
Weight	2.35 kg

**UNPACK &
GET STARTED**
Triple Interface Integrated

LABEL
SOFTWARE
INCLUDED



Drivers
by Seagull™

L-42DT
METAPACE